

Portable Receiving JS5100A

Interconnection with portable JS5500 series device network



Wireless&RS-485



Data processing



Data storage



Support 64 Intelligent temperature and power meter



JS5100A Portable Receiving

* Patent No.: ZL2019304232374

- High quality shell ——Glass screen
- 100ch can setup
- 32MByte
- Support data collection for offline
- Communication range: 300m
- Wireless networking

Specifications

Communication mode	Wireless/RS-485	Data write rate	2Hz
Channels	100ch (can setup)	Data update rate	≥300ms
Communications range	300m,line of sight	Operating power input	DC5V-1A, USB interface
Maximum transmitting power	20dBm	Power consumption	≤0.8W
Communication band	ISM 433.4~473.0MHz	Operating temp.	0°C~50°C
Air baud rate	9600bps	Storage temp.	-20°C~55°C
Operating frequency	40MHz	Operating humidity	20%~85% (No condensating)
Wireless acquisition	300ms	Operating altitude	0~3000m
High-speed acquisition	100ms	Dimensions	100mm*65mm*20.8mm
Offline collection	500ms	Compliant standard	GB/T 13978-2008
Data memory	400 thousand groups	Intellectual property	*Patent No.: ZL2019304232374

Configuration


A# JS5508S Intelligent temperature and power meter*N + JS5100A Portable Receiving *1 + Portable MixViewer*1

B# JS5508S *N + JS5501C Intelligent power meter *N + ... + JS5100A *1 + Portable MixViewer*1

Guangzhou Jingsheng Electronic Technology Co., Ltd.

Address: 121-122, Block 34 Gongmeigang International Innovation Center,
No. 2519 Xingang East Road, Haizhu District, Guangzhou, China

Website: www.jimstech.cn Hotline: 400-806-1920



Ver 1.0 201911